

Access Rights

Access Rights

The Access Rights plug-in tool allows access rights checks to be performed outside of Rosetta. On checking the access rights, the plug-in returns a true or false value that controls whether an object can be viewed.

Plug-in Parameters

Depending on the specific implementation, a plug-in may or may not require parameters. If the plug-in does require parameters, they are populated during installation of a new instance of the plug-in.

Usage

The Access Rights plug-in is available as input criteria on the access rights configuration page.

MID	1	Metadata Type	policy, policy:accessrights, accessrights	Description	Only 5 concurrent users may view this object
Created by	SYSTEM	Creation Date	31/05/2021 19:06:27		
Updated by	SYSTEM	Update Date	31/05/2021 19:06:27		

New Group
 To Existing Group

Select Group: 1

Criteria: AR Plug-in
Operator: equal
Value 1:

Cancel Save

Access Rights Plug-in Configuration

The plug-in relies on two properties:

1. Token – This should be concatenated to the delivery URL (created by the external system accessing Rosetta) and will be used by the plug-in.

Example:

```
http://rosetta.exlibrisgroup.com:1801/delivery/DeliveryManagerServlet?dps_pid=IE17978/delivery/  
DeliveryManagerServlet?dps_pid=IE17978&token=<token>
```

2. IP - The IP address is derived from the General Parameter `client_ip_header` (similar to any other IP-based access right functionality).

Implementations

There are no implementations for the Access Rights plug-in.