
Additional IDs in the Patron List (cir-05) report

- **Article Type:** Q&A
 - **Product:** Aleph
-

Question

Is it possible to display the additional IDs in the Patron List (cir-05) report?

Answer

Yes

Additional Information

The borrower-list-report.xls reports that are used for this service are located in the ./xxx50/form_Ing (or xxx01/form_Ing) directory or whatever location is the default. (This form_Ing location can be checked in the ./xxx50/tab/path_convert.)

The z302-key-0x should correspond to the 0x type of ID used at the library.

The label can be edited to describe the type of ID (LDAP, Campus, etc.).

Below is a sample report (borrower-List-report-03.xml) with additional IDs:

```
<xsl:stylesheet
xmlns:xsl="http://www.w3.org/1999/XSL/Transform" version="1.0">
<xsl:output method="xml" indent="yes"/>
```

```
<xsl:include href="funcs.xml"/>
```

```
<xsl:template match="/">
<xsl:call-template name="header"/>
```

```
<!--section-02 (GRID)-->
<xsl:for-each select="//section-02">
<xsl:if test="position() = 1">
<xsl:call-template name="section-02">
<xsl:with-param name="header" select=""header""/>
</xsl:call-template>
</xsl:if>
<xsl:call-template name="section-02"/>
</xsl:for-each>
```

```
</xsl:template>
```

```
<!-- START DATA -->
```

```
<xsl:template name="header">  
<xsl:call-template name="header-gen">  
<xsl:with-param name="title" select="'Patron List Report'"/>  
</xsl:call-template>  
</xsl:template>
```

```
<!--SECTION-02 (GRID)-->
```

```
<xsl:template name="section-02">  
<xsl:param name="header"/>  
<xsl:if test="$header!="">  
<xsl:call-template name="start-grid"/>  
</xsl:if>  
<xsl:call-template name="table-start-row"/>  
<xsl:call-template name="display-grid-gen">  
<xsl:with-param name="label" select="'Patron Barcode'"/>  
<xsl:with-param name="value" select="./z308-key-data"/>  
<xsl:with-param name="type" select="'barcode'"/>  
<xsl:with-param name="header" select="$header"/>  
</xsl:call-template>  
<xsl:call-template name="display-grid-gen">  
<xsl:with-param name="label" select="'Patron Name'"/>  
<xsl:with-param name="value" select="./z303-name"/>  
<xsl:with-param name="header" select="$header"/>  
</xsl:call-template>  
<xsl:call-template name="display-grid-gen">  
<xsl:with-param name="label" select="'Patron Status'"/>  
<xsl:with-param name="value" select="./z305-bor-status"/>  
<xsl:with-param name="header" select="$header"/>  
</xsl:call-template>  
<xsl:call-template name="display-grid-gen">  
<xsl:with-param name="label" select="'Phone No.'"/>  
<xsl:with-param name="value" select="./z304-telephone"/>  
<xsl:with-param name="header" select="$header"/>  
</xsl:call-template>  
<xsl:call-template name="display-grid-gen">  
<xsl:with-param name="label" select="'Patron ID'"/>  
<xsl:with-param name="value" select="./z303-id"/>  
<xsl:with-param name="header" select="$header"/>  
</xsl:call-template>  
<xsl:call-template name="display-grid-gen">  
<xsl:with-param name="label" select="'LDAP ID'"/>  
<xsl:with-param name="value" select="./z302-key-07"/>
```

```
<xsl:with-param name="header" select="$header"/>
</xsl:call-template>
<xsl:call-template name="display-grid-gen">
<xsl:with-param name="label" select="Campus ID"/>
<xsl:with-param name="value" select="/z302-key-04"/>
<xsl:with-param name="header" select="$header"/>
</xsl:call-template>
<xsl:call-template name="table-end-row"/>
</xsl:template>
</xsl:stylesheet>
```

Category: Circulation (500)

Subject: Patrons

- **Article last edited:** 10/8/2013