
"Library Has" holdings fields display twice in Tomcat

- **Article Type:** General
 - **Product:** Voyager
 - **Product Version:** 7.2.2
-

Problem Symptoms:

- "Library Has" holdings fields display twice in Tomcat OPAC.
- MARC 866 fields are not duplicated in holdings records in Cataloging.

Cause:

File displayHoldings.xml has redundant specifications for 866 field display.

Resolution:

Edit /m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xsl/contentLayout/configs/displayHoldings.xml to remove redundant specifications for MARC 866 display.

*See the "See Also" section at the bottom of this article.

Additional Information

Example 1a: OPAC display with redundant "Library Has" display data:

Number of items: 150
Status: Not Charged
Library Has: v.1-160 (1988-2011)
v.1-160 (1988-2011)

Example 1b: displayHoldings.xml containing redundant display data.

Note: in the example below, the top 866 line "<displayTag field="866" indicator1="|" indicator2="|" subfield="az" />" is redundant with subsequent ones with spelled-out indicators causing a duplicate display of the "Library Has" data.

```
<holdingsTags label="Current Issues:">  
<displayTag field="866" indicator1="|" indicator2="|" subfield="az" /> << displays 866 fields  
<displayTag field="1020" />  
</holdingsTags>
```

```
<holdingsTags label="Library Has:">  
<displayTag field="1040" />
```

```

<displayTag field="866" indicator1="|" indicator2="0" subfield="az" /> << redundant with top displayTag line
<displayTag field="866" indicator1="|" indicator2="1" subfield="az" /> << redundant with top displayTag line
<displayTag field="866" indicator1="|" indicator2="2" subfield="az" /> << redundant with top displayTag top line
<displayTag field="866" indicator1="3" indicator2="0" subfield="az" /> << redundant with top displayTag top line
<displayTag field="866" indicator1="3" indicator2="1" subfield="az" /> << redundant with displayTag line
<displayTag field="866" indicator1="3" indicator2="2" subfield="az" /> << redundant with top displayTag line
<displayTag field="866" indicator1="4" indicator2="0" subfield="az" /> << redundant with top displayTag line
<displayTag field="866" indicator1="4" indicator2="1" subfield="az" /> << redundant with top displayTag line
<displayTag field="866" indicator1="4" indicator2="2" subfield="az" /> << redundant with top displayTag line
<displayTag field="866" indicator1="5" indicator2="0" subfield="az" /> << redundant with top displayTag line
<displayTag field="866" indicator1="5" indicator2="1" subfield="az" /> << redundant with top displayTag line
<displayTag field="866" indicator1="5" indicator2="2" subfield="az" /> << redundant with top displayTag line
<displayTag field="899" indicator1="X" indicator2="X" subfield="a" /> << redundant with top displayTag line
</holdingsTags>

```

Example 2a: OPAC display without redundant "Library Has" display data:

Number of items: 150

Status: Not Charged

Library Has: v.1-160 (1988-2011)

Example 2b: displayHoldings.xml with redundancy commented out:

```

<holdingsTags label="Current Issues:">
<displayTag field="866" indicator1="|" indicator2="|" subfield="az" />
<displayTag field="1020" />
</holdingsTags>

```

```

<holdingsTags label="Library Has:">
<displayTag field="1040" />
<!--
<displayTag field="866" indicator1="|" indicator2="0" subfield="az" />
<displayTag field="866" indicator1="|" indicator2="1" subfield="az" />
<displayTag field="866" indicator1="|" indicator2="2" subfield="az" />
<displayTag field="866" indicator1="3" indicator2="0" subfield="az" />
<displayTag field="866" indicator1="3" indicator2="1" subfield="az" />
<displayTag field="866" indicator1="3" indicator2="2" subfield="az" />
<displayTag field="866" indicator1="4" indicator2="0" subfield="az" />
<displayTag field="866" indicator1="4" indicator2="1" subfield="az" />
<displayTag field="866" indicator1="4" indicator2="2" subfield="az" />
<displayTag field="866" indicator1="5" indicator2="0" subfield="az" />
<displayTag field="866" indicator1="5" indicator2="1" subfield="az" />
<displayTag field="866" indicator1="5" indicator2="2" subfield="az" />
<displayTag field="899" indicator1="X" indicator2="X" subfield="a" />
-->
</holdingsTags>

```

See also:

[Recent Issues display twice and include the journal title in Voyager WebVoyage](#)

Webvoyage Architecture Overview and Configuration Models and KB item 16384-57682.

- Article last edited: 10/8/2013