
Incomplete sublibrary address on plain Overdue summary letter

- **Article Type:** General
 - **Product:** Aleph
 - **Product Version:** 20
-

Problem Symptoms:

- * The library's address that appears in the body of the e-mail is not full, i.e., only the first seven lines are displayed so telephone and fax are excluded.
- * The address in the file tab_sub_library_address.lng correctly has telephone and fax

Cause:

The relevant lines are missing in the xsl template

Resolution:

To include all 9 lines from the sublibrary address on the overdue e-mail:

1. modify the xsl template "plain-funcs-address.xsl" as follows:

```
<xsl:template name="sublib-address">
<xsl:call-template name="new-line"/>
<xsl:value-of select="//sub-library-address-1-occ1"/><xsl:call-template name="new-line"/>
<xsl:value-of select="//sub-library-address-1-occ2"/><xsl:call-template name="new-line"/>
<xsl:value-of select="//sub-library-address-1-occ3"/><xsl:call-template name="new-line"/>
<xsl:value-of select="//sub-library-address-1-occ4"/><xsl:call-template name="new-line"/>
<xsl:value-of select="//sub-library-address-1-occ5"/><xsl:call-template name="new-line"/>
<xsl:value-of select="//sub-library-address-1-occ6"/><xsl:call-template name="new-line"/>
<xsl:value-of select="//sub-library-address-1-occ7"/><xsl:call-template name="new-line"/>
</xsl:template>
```

--> add lines

```
<xsl:value-of select="//sub-library-address-1-occ8"/><xsl:call-template name="new-line"/>
<xsl:value-of select="//sub-library-address-1-occ9"/><xsl:call-template name="new-line"/>
```

2. Use util i/6 to recreate the print template package

Category: Circulation (500)

Subject: Printing

- **Article last edited:** 10/8/2013