

How do I allow notes to display in the OPAC?

- **Article Type:** General
- **Product:** Voyager
- **Product Version:** 7.1.0

Question

How to display bibliographic note fields in OPAC?

Answer

1. **Edit** `/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xsl/contentLayout/configs/displaycfg.xml`
2. **Uncomment entire** `displayTags` stanza for "Notes"
3. Comment out lines for fields that should not be displayed, leaving line for desired field active

Always backup your file before making any changes.

Additional Information

Example: `displaycfg.xml` section after changes to allow display of 520 field and add the 590 field:

```
<!-- displayTags label="Notes:" -->
<!--
<!--
<displayTag field="500" indicator1="X" indicator2="X" subfield="a"/>
<displayTag field="501" indicator1="X" indicator2="X" subfield="a"/>
<displayTag field="502" indicator1="X" indicator2="X" subfield="a"/>
<displayTag field="504" indicator1="X" indicator2="X" subfield="ab"/>
<displayTag field="506" indicator1="X" indicator2="X" subfield="abcde"/>
-->

<!-- Uncommented note field below to allow 520 to display -->
<displayTag field="520" indicator1="X" indicator2="X" subfield="ab"/>

<!-- Add field below to allow 590 to display -->
<displayTag field="590" indicator1="X" indicator2="X" subfield="a"/>

<!--
<displayTag field="525" indicator1="X" indicator2="X" subfield="a"/>
<displayTag field="530" indicator1="X" indicator2="X" subfield="a"/>
<displayTag field="533" indicator1="X" indicator2="X" subfield="ae"/>
<displayTag field="538" indicator1="X" indicator2="X" subfield="a"/>
<displayTag field="540" indicator1="X" indicator2="X" subfield="abcd"/>
<displayTag field="545" indicator1="X" indicator2="X" subfield="ab"/>
<displayTag field="546" indicator1="X" indicator2="X" subfield="ab"/>
<displayTag field="555" indicator1="X" indicator2="X" subfield="ab"/>
```

```
<displayTag field="697" indicator1="X" indicator2="X" subfield="a"/>
<displayTag field="698" indicator1="X" indicator2="X" subfield="a"/>
<displayTag field="699" indicator1="X" indicator2="X" subfield="a"/>
-->
</displayTags>
```

See Also: [Acceptable codes for MARC indictor fields in Voyager displaycfg and displayHoldings XML files](#)

- **Article last edited:** 08-Dec-2019