
Cluster/Facet Customization in MetaLib 4.0x, SP123

- **Article Type:** General
 - **Product:** MetaLib
 - **Product Version:** 4
-

Description:

Starting from SP 123 some aspects of the Cluster/Facets functionality are customizable.

Resolution:

For Cluster/Facet Customization, for all local instances and all languages:

(1) Please, note that the changes mentioned in section (1) for the html file `www_const.<lng>` are only relevant for the sites where the MetaLib Upgrade Express was applied.

In the `./insNN/tab/www_const.<lng>`, add the following terms under the Cluster/Facet section:

TOPICS -- Topics
DATES -- Dates
AUTHORS -- Authors
JOURNAL TITLES -- Journal Titles
SUBJECTS -- Subjects
DATABASES -- Databases
After -- After
Before -- Before

These additions can also be seen in "MetaLib Version 4.0x - How to Customize Cluster-Facets" document (attached)

(2) In the file `./insNN/js/Clustering.js`:

Replace the line, in the function HideAll

```
if ( imgIdStr.indexOf("c1_Plus") > -1 )
```

with

```
if ( imgIdStr.indexOf("_Plus") > -1 )
```

Replace the line, in the function OpenSelected

```
document.getElementById("c1_Plus" + display_id).src=icon_path + '/v-icon_minus.png';
```

with

```
document.getElementById(cluster_id + "_Plus" + display_id).src=icon_path + '/v-icon_minus.png';
```

Additional Information

Cluster Facet, customization, settings

- **Article last edited:** 10/8/2013