

---

## Coding tab\_sfx for multiple services

- **Article Type:** General
  - **Product:** Aleph
  - **Product Version:** 18.01
- 

### Description:

I've set up our training web opac to show an SFX button \*if\* there's fulltext available. My tab\_sfx says:

```
TEST www_f_sfx 11 N getFullTtxt
```

In order to add another service, say, getDocumentDelivery, how do I update the table? Like this (i.e. with an additional line):

```
TEST www_f_sfx 11 N getFullTtxt  
TEST www_f_sfx 11 N getDocumentDelivery
```

or:

```
TEST www_f_sfx 11 N getFullTtxt getDocumentDelivery
```

### Resolution:

You want to use two lines for this, rather than one. In the v.18 System Librarians Guide for Web OPAC, p. 51, it states:

"If more than one SFX service is required, columns 1-4 do not have to be repeated. For example:

```
USM01 www_f_sfx 11 N getAuthorEmail  
getCitedJournal
```

means that either getAuthorEmail or getCitedJournal have to be available for the www\_f\_sfx icon to be displayed."

So, I interpret this as meaning that multiple services for the same base should be on separate lines. The information in columns 1-4 need not be repeated, but probably can be without harm, if you prefer.

---

- **Article last edited:** 10/8/2013