
Error: ... is not allowed in \$data_tab/tab100 of library

- **Article Type:** General
 - **Product:** Aleph
 - **Product Version:** 17.01
-

Description:

In running a job, dlib-ing to a library, etc., you get "Error: ... is not allowed in \$data_tab/tab100 of library " messages, such as:

Error: Z01-TAG-SENSITIVE is not allowed in \$data_tab/tab100 of library ABC50.

Error: USER-HOME-PERMISSION is not allowed in \$data_tab/tab100 of library ABC50.

Error: PDS-AWARE is not allowed in \$data_tab/tab100 of library ABC50.

Error: ILL-MODE is not allowed in \$data_tab/tab100 of library USM40

Resolution:

Certain tab100 parameters can be included only in the shared \$alephe_tab/tab100, not in the \$data_tab/tab100 of an individual library.

The tab100 header entry for such parameters contains this line:

```
!# tab100 of library: No;...
```

As long as the \$alephe_tab/tab100 has the correct value for the parameter, these messages can be ignored -- but it is better to remove them from the \$data_tab/tab100 -- to avoid confusion.

The \$alephe_tab-only parameters are (for v18):

ALPHA-NUMERIC-PASSWORD

FIRST-LOGIN-PASS-CHANGE

FRENCH-AUT

ILL-MODE

MINIMUM-PASSWORD-LENGTH

PASSWORD-CHANGE-PERIOD

PASSWORD-FAIL-BLOCK

PASSWORD-NO-USE-PERIOD

PDS-AWARE

PLAIN-ONLY

USER-HOME-PERMISSION

Z01-TAG-SENSITIVE

Additional Information

tab100, faq

- **Article last edited:** 10/8/2013