

---

## How to use AutoUpdate to distribute different clients?

- **Article Type:** General
  - **Product:** Voyager
- 

### Question

How to distribute SysAdmin client to some users via AutoUpdate, but not others?

### Answer

Create separate AutoUpdate directory & path for those users:

1. Connect via SSH to server as voyager user.
2. `cd /m1/voyager/clients/autoupdate`
3. `cp -pr voyager sysadmin` Result : a new AutoUpdate directory called (in this example) sysadmin (/m1/voyager/clients/autoupdate/sysadmin) which is a copy of voyager (/m1/voyager/clients/autoupdate/voyager) AutoUpdate directory.
4. `cd sysadmin`
5. Edit `update.txt` to include `\SysAdmin.exe` and `\SysAdmin.chm`
6. Ensure `SysAdmin.exe` and `SysAdmin.chm` are in sysadmin directory.
7. `cd ../voyager` and ensure SysAdmin files are not included in update.txt for other users.
8. Set `[Upgrade]` stanza in voyager.ini file on the PCs that will receive SysAdmin client so that it points to the new directory.

```
[Upgrade]
Voyager=http://<user>:<password>@<server IP>:7099/autoupdate/sysadmin/
```

---

### Note

With increased security of Windows systems, AutoUpdate has become increasingly problematic to implement and support. In some environments it no longer works. Support recommends you consider different options/methods for installing new clients.

---

---

### Additional Information

See Technical User's Guide, "[Upgrade] Stanza - Voyager 8 and Later"

---

- **Article last edited:** 26-Apr-2016