
How is the WWW_HOST variable, set in aleph_start, used?

- **Article Type:** General
 - **Product:** Aleph
 - **Product Version:** 20
-

Description:

How is the WWW_HOST variable, set in aleph_start, used?

Resolution:

When the GUI wants to access the www_server, it uses WWW_HOST as the address.

global_grep shows that WWW_HOST is used in the following programs:

```
"WWW_HOST"
```

```
file above is: ./butil/b_sdi_01_a.cbl
```

```
"WWW_HOST"
```

```
file above is: ./danzg_ill/danzg_ill_doc_to_apdu_ext.cbl
```

```
"WWW_HOST"
```

```
file above is: ./expand_doc/expand_doc_bib_z403.cbl
```

```
"WWW_HOST"
```

```
file above is: ./expand_doc/expand_doc_link_to_doc.cbl
```

```
MOVE "WWW_HOST" TO ENV-NAME.
```

```
file above is: ./ill_x_service/ill_x_locate.cbl
```

```
"WWW_HOST"
```

```
file above is: ./iso_ill/iso_ill_doc_to_apdu_extensions.cbl
```

```
"WWW_HOST"
```

```
file above is: ./pc_com/pc_com_get_www_addr.cbl
```

```
sprintf (email_str_sender,"%s@%s",getenv ("USER"),getenv("WWW_HOST"));
```

```
file above is: ./tlc/illclient/ill_out_message_smtp.cpp
```

```
"WWW_HOST"
```

```
file above is: ./www_f/www_f_bor_sdi_update.cbl
```

- **Article last edited:** 10/8/2013