
Oracle shutdown and startup scripts

- **Article Type:** General
 - **Product:** Aleph
 - **Product Version:** 20, 21, 22, 23
-

Description:

I would like to shutdown Oracle for this weekend and I would like to practice with our startup and shutdown. I don't see where it shutdown Oracle, can someone look at this for me when they get a chance and if Oracle is not getting shutdown, let me know what values to give for an Oracle shutdown.

Resolution:

Note: Oracle restart needs to be preceded by aleph_shutdown and followed by aleph_startup. See the article "[Proper way to restart Oracle on an Aleph server](#)" in this regard. As described in the article, in an "All-in-One" setup, Oracle can be restarted using util o/1/2 .

Or:

Login as user oracle

Run command

```
$ dbshut
```

It's located in \$ORACLE_HOME/bin. or

run

```
$ svrmgrl > connect internal > shutdown immediate {Oracle shutdown is not supposed to be included into aleph shutdown.}
```

Oracle startup and shutdown script are \$ORACLE_HOME/bin/dbstart and \$ORACLE_HOME/bin/dbshut.

It's a responsibility of sysadmin to create system script which calls those scripts when the server starts and stops.

Additional Information

Oracle, shutdown, startup, scripts

- **Article last edited:** 10/8/2013