
Disable localhost_access logging in Digitool

Overview

In Digitool JBOSS generates an access log daily named like this; localhost_access_log.2015-11-16.log in the jb_log path.

If these logs are causing disk space issues, you may wish to set up a scheduled task to delete older logs. If the size is still an issue you may wish to disable access logging altogether.

To Disable Logging..

First Step - Edit xml file

Access logging can be disabled by editing the server.xml using the vi editor:

```
>jb_deploy  
>cd jbossweb-tomcat.sar  
>vi server.xml
```

To disable logging, comment out this section in server.xml by adding the BOLD highlighted lines

```
<!-- Access logger -->  
<!-- Access logging disabled  
    <Valve className="org.apache.catalina.valves.AccessLogValve"  
        prefix="localhost_access_log." suffix=".log"  
        pattern="common" directory="{jboss.server.home.dir}/log"  
        resolveHosts="false" />  
-->
```

Second Step - Restart JBOSS

JBOSS must be restarted in order for the configuration to take effect:

To shut down JBOSS

```
$jdtlh_bin/jboss_shutdown.sh
```

To start JBOSS

```
$jdtlh_bin/jboss_startup.sh
```

(This will result in a minute or two of downtime)

Warning

There is no facility to change the logging level. Logging is either "on" or "off".