

---

## OPAC search "Multi fields"

- **Product:** Aleph
  - **Product Version:** 20, 21, 22, 23
  - **Relevant for Installation Type:** Dedicated-Direct, Direct, Local, Total Care
- 

### Problem:

In multi field search you can fill in search terms for

Author

Title

Year

Publisher

When filling in a term in field "Publisher" and you get no hits the term moves to field "Year". When filling in a term in field "Year" it moves to "Title" when no record is found.

### Cause:

Configuration

### Resolution:

In table \$alephe\_root/www\_f\_ing the fields for the multi field search are configured. Every single entry has a variable (\$0100, \$0200, \$0300 etc.). And none of this variables must be missing! In below example you can see that the part „Title, browse„ is commented out and therefore the value \$0300 is missing. The following entries should be renumbered so that no value is missing meaning Title will be \$0300 instead of \$0400, Year will be \$0400 instead of \$0500 etc.

```
<tr>
<th class=td2 align=left width=10% nowrap>Schlagwort </th>
<td class=td2 id="small">
<input type="hidden" size=13 name=find_code value="WSW">
<input size=35 name=request value="$0100">
</td>
</tr>
<tr>
<th class=td2 align=left>Author</th>
<td class=td2 id="small">
<input type="hidden" size=3 name=request_op value="AND">
<input type="hidden" size=6 name=find_code value="WPE">
<input size=35 name=request value="$0200">
</td>
```

```

</tr>

<!--
<tr>
<th class=td2 align=left>Title, browse</th>
<td class=td2 id="small">
<input type="hidden" size=3 name=request_op value="AND">
<input type="hidden" size=5 name=find_code value="PTI">
<input size=35 name=request value="$0300">
<span class="text1">(Start with a word in the title) </span>
</td>
</tr>
-->

<tr>
<th class=td2 align=left>Title</th>
<td class=td2 id="small">
<input type="hidden" size=3 name=request_op value="AND">
<input type="hidden" size=5 name=find_code value="WTI">
<input size=35 name=request value="$0400">
</td>
</tr>
<tr>
<th class=td2 align=left>Year</th>
<td class=td2 id="small">
<input type="hidden" size=3 name=request_op value="AND">
<input type="hidden" size=4 name=find_code value="WYR">
<input size=35 name=request value="$0500">
</td>
</tr>
<tr>
<th class=td2 align=left>Publisher</th>
<td class=td2 id="small">
<input type="hidden" size=3 name=request_op value="AND">
<input type="hidden" size=11 name=find_code value="PVE">
<input size=35 name=request value="$0600">
</td>

```

---

• **Article last edited:** 6-Jun-2016