

---

## OPAC: WebVoyage 7 (Tomcat) Numbered Search Results

Created By: Jim Robinson  
Created on: 5/14/2019

[This article was copied from the Voyager Wiki.]

---

### Description

Numbers the search results in WebVoyage 7 (Tomcat)

---

### Installation Instructions

In ui/[skin]/xsl/pageFacets/resultsFacets.xsl, find this:

```
<!-- ## result record ## -->

<div class="{ $classPosition }">

    <xsl:if test="$buttonCount > 0">

        <!-- ## checkbox ## -->

            <div class="resultListCheckBox">

                <input type="checkbox" name="titles" value="{page:value}" id="{page:value}"
onClick="selectTitleChkBx (document.getElementById('resultsForm'))">

                    <xsl:if test="@selected='true'">

                        <xsl:attribute name="checked">checked</xsl:attribute>

                    </xsl:if>

                </input>

            </div>

        </xsl:if>

        <xsl:variable name="checkBoxId">

            <xsl:value-of select="page:value"/>

        </xsl:variable>

    </div>

</xsl:if>
```

```
</xsl:variable>
```

and change it to this (the changes are after </input>):

```
<!-- ## result record ## -->
```

```
<div class="{ $classPosition }">
```

```
<xsl:if test="$buttonCount > 0">
```

```
<!-- ## checkbox ## -->
```

```
<div class="resultListCheckBox">
```

```
<input type="checkbox" name="titles" value="{page:value}" id="{page:value}"
onClick="selectTitleChkBx (document.getElementById('resultsForm'))">
```

```
<xsl:if test="@selected='true'">
```

```
<xsl:attribute name="checked">checked</xsl:attribute>
```

```
</xsl:if>
```

```
</input>
```

```
<xsl:if test="string-length(//page:element[@nameId='recPointer']/page:value)">
```

```
<xsl:value-of select="position() + //page:element[@nameId='recPointer']"/>
```

```
</xsl:if>
```

```
</div>
```

```
</xsl:if>
```

```
<xsl:variable name="checkBoxId">
```

```
<xsl:value-of select="page:value"/>
```

```
</xsl:variable>
```

The screenshot shows a library interface with a table of search results. The table has two columns: one for the search results and one for actions. The first row shows a search result for 'Corrosion of Medicine' by Greynan, John, M.D. / Angell, Marcia (FRW) with no call number and no item information. The second row shows a search result for 'Medicine meets virtual reality 14 [electronic resource] : accelerating change in healthcare : next medical toolkit / edited by James D. Westwood ... [et al.]' with a link to the author's homepage (http://library.tccd.edu) and a download button. The download button is currently disabled, showing 'Nothing to download...'. The interface is titled 'Screen captures' and 'Working example'.

## Installation instructions

In [ui/skin/xsl/pageFacets/resultsFacets.xsl](#), find this:

```
<div class="{classPosition}">
  <xsl:if test="$buttonCount > 0">
    <div class="resultListCheckBox">
      <input type="checkbox" name="titles" value="{page:page}" id="{page:page}"
onClick="selectFileChkBx(document.getElementById('resultsForm'))">
      <xsl:if test="$selected='true'">
        <xsl:attribute name="checked">checked</xsl:attribute>
      </xsl:if>
    </input>
  </div>
</xsl:if>
<xsl:variable name="checkboxBoxId">
  <xsl:value-of select="page:page"/>
</xsl:variable>
```

and change it to this (the changes are after <input>):

```
<div class="{classPosition}">
  <xsl:if test="$buttonCount > 0">
    <div class="resultListCheckBox">
      <input type="checkbox" name="titles" value="{page:page}" id="{page:page}"
onClick="selectFileChkBx(document.getElementById('resultsForm'))">
      <xsl:if test="$selected='true'">
        <xsl:attribute name="checked">checked</xsl:attribute>
      </xsl:if>
      </input>
      <xsl:if test="string-length(//page:element[@nameId='recPointer']/page:page)">
        <xsl:value-of select="position() + //page:element[@nameId='recPointer']"/>
      </xsl:if>
    </div>
  </xsl:if>
<xsl:variable name="checkboxBoxId">
  <xsl:value-of select="page:page"/>
</xsl:variable>
```

## Report