
OPAC: Adding Exit Session Navigation

Created By: Laura Guy
Created on: 5/14/2019

[This article was copied from the Voyager Wiki.]

Introduction

This relates to the "New" Tomcat WebVoyage that is included in Voyager 7.0.1 and forward.

Our users were accustomed to having an "Exit" button available to them on the "Classic" interface. In public lab situations we encourage them to use it when they leave a workstation. To add a similiar functionality to the "New" WebVoyage you can add the following code to the appropriate two files. See the screenshot example at the bottom of this document.

Top Navigation Exit Button

1) To add the top option edit /m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/your_SKIN/xsl/pageFacets/header.xsl

Edit the BOTTOM of the file to include the "adds an exit button" code in between the two comment lines:

```
<!-- This modification adds an exit button to the header tabs YYYY/MM/DD -->
    <li class="off" title="Exit Session">
        <a href="exit.do" name="Exit Button">
            <span>Exit Session</span>
        </a>
    </li>
<!-- End modification to add an exit button -->

</ul>
</div>
</xsl:for-each>
</div>
</xsl:for-each>
</xsl:template>
```

REMEMBER to update the comments section at the top of the file!

Bottom Navigation Exit Button

2) To add the bottom option edit footer.xml in the same directory as the header.xml file

Add the "extra footer tabs" section between the comments as shown below. Change the URL appropriately.

```
<xsl:template name="buildFooter">

<xsl:for-each select="/page:page/page:pageFooter">
<div id="pageFooter">
<xsl:for-each select="page:tabs[@nameId='page.footer.buttons']">

<div id="footerTabs" title="{ $footerText/footerTabs} ">
<a name="navFooter"></a>
<h2 class="navFooter"><xsl:value-of select="$footerText/footerTabs"/></h2>
<ul class="navbar">
<!--\- extra footer tabs \-->
<li>
<a href="http://www.mines.edu/library" title="Exit Session">Exit Session</a>
</li>
<!--\- end of extra footer tabs \-->
<xsl:for-each select="$Configs/pageConfigs/footerTabDisplayOrder/tab">
<xsl:variable name="tempName" select="@name"/>
<xsl:variable name="newWin" select="@clickOpensNewWindow"/>
<xsl:call-template name="buildFooterTab">
<xsl:with-param name="displayTab" select="$tempName"/>
<xsl:with-param name="newWin" select="$newWin"/>
</xsl:call-template>
</xsl:for-each>
</ul>
</div>

</xsl:for-each>
```

```
<div id="libraryLink">
<span>
<xsl:call-template name="buildLinkType">
<xsl:with-param name="eleName"&nbsp; select="'page.footer.library.link'"/>
</xsl:call-template>
</span>
</div>
```

*REMEMBER to update the comments section at the top of the file!

Important Caveat

Future changes in the UI may break these instructions.

[Report](#)